



## Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

[www.freezerlink.com](http://www.freezerlink.com)

### FR2004001 Flammable Storage Refrigerator

24 cubic feet, 1 solid door – Energy Star Qualified

#### Standard Product Features:

- UL and C-UL listed; CEC California Energy Commission; **Energy Star**
- Adjustable control range **2°C to 10°C**
- Factory preset at 4°C.
- Internal chamber thermometer
- Exterior front, sides, back and door are white baked on enamel
- The exterior top and bottom are galvanized steel.
- Interior liner and interior door panel are smooth aluminum.
- Cabinet and doors are foamed-in-place with **CFC Free** high density polyurethane foam insulation.
- Heavy duty spring loaded hinges.
- Key lock door.
- Full length stainless steel pull handles.
- **Four casters (2 locking).**
- 3 epoxy coated wire shelves.
- **Manual defrost.**
- Complete top mount refrigeration system.
- Cold wall evaporator.
- Air-cooled condensing unit.
- Self closing solid door.
- Magnetic door gasket.
- Door opening heaters.
- **Warranties:** 18 month parts and labor, 5 year compressor (US and Canada) 18 months parts (International).



#### Specifications - FR2004001 Flammable Storage Refrigerator

<b>Interior Height</b>	59" (149.9 cm)
<b>Interior Width</b>	23-1/2" (59.7 cm)
<b>Interior Depth</b>	30" (76.2 cm)
<b>Overall Height*</b>	80-3/8" (204.2 cm)
<b>Overall Width</b>	27-1/2" (69.9 cm)
<b>Overall Depth</b>	34-7/8" (88.6 cm)



## Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

[www.freezerlink.com](http://www.freezerlink.com)

### FR2004001 Flammable Storage Refrigerator

24 cubic feet, 1 solid door (continued)

<b>Gross Cu. Ft.</b>	24 (0.68 cu.m.)
<b>Shelf Area (sq.ft.)</b>	12.8 (1.19 sq.m.)
<b>Number of Shelves</b>	3
<b>Number of Casters</b>	4 Standard
<b>Number of Legs</b>	4 Optional
<b>Condensing Unit</b>	1/4 HP
<b>Refrigerant</b>	R404A
<b>Electrical</b>	115/60/1
<b>Cord &amp; Plug</b>	Yes
<b>Max Fuse Size</b>	15
<b>NEMA Plug</b>	5-15P
<b>Total Amp Draw</b>	6.4

**Voltage:** 115V 1PH 60HZ Plug Type 5-15P

<b>Crated Height</b>	83-3/4" (212.7 cm)
<b>Crated Width</b>	37" (94.0 cm)
<b>Crated Depth</b>	41" (104.0 cm)
<b>Crated Weight</b>	382 (173.6 kg)

#### Options for FF2004001

LEGS	Legs in lieu of casters
BIN	Storage bin 23 x 4 x 4
EXTSS	SS Exterior (with galv. back)
SHELFNSXF	Extra shelf with clips
INTSS	Stainless steel interior
SSDRAWER	SS drawer (8 per door)
THERMALARM	Field Installed(field installed)
REC6DP1	Temp chart recorder/chart paper
Export Crating	For <b>FF2004005</b>