



Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

www.freezerlink.com

GPRM1S24 General Purpose Refrigerator Manual Defrost 4°C 24 Cu Ft

External Dimensions:

27-1/2"W x 34-7/8"D x 80-3/8"H

Internal Dimensions:

23-1/2"W x 30"D x 59"H

Standard GPRM1S24 General Purpose Refrigerator Manual Features:

- Adjustable control range from 2°C to 8°C
Factory preset at 4°C.
- Internal chamber thermometer
- The exterior front, sides, back and door are white baked on enamel
- The exterior top and bottom are galvanized steel
- Interior liner and interior door panel are smooth aluminum
- Cabinet and doors are foamed-in-place with CFC Free high density polyurethane foam insulation, heavy duty spring loaded hinges, key lock door
- Full length stainless steel pull handles
- Four casters (2 locking)
- 3 epoxy coated wire shelves
- Complete top mount refrigeration system, with Cold wall evaporator, air-cooled condensing unit
- Self closing solid door, magnetic gasket, door opening heaters
- **Warranty:** 18 month parts and labor, 5 year compressor (US and Canada) 18 months parts (International)
- **UL and C-UL listed;** CEC California Energy Commission; Energy Star



GPRM1S24 General Purpose Refrigerator Manual Options:

- Legs in lieu of casters
- Extra shelf with clips
- Stainless steel exterior (with galv. back)
- Stainless steel interior
- Stainless steel drawer (max. 8 per door)
- Wire basket drawer (max. 6 per door)
- Temperature chart recorder with chart paper
- Digital thermometer monitor with alarm (field Install)
- Export crating

www.freezerlink.com