



## Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

[www.freezerlink.com](http://www.freezerlink.com)

### **RIBOD1S20 - Refrigerated Incubator /BOD Chamber -10°C to 50°C/ One Door 20 Cubic Ft. 115V, 60Hz**

#### **External Dimensions:**

32"W x 28-1/2"D x 80-3/8"H

#### **Internal Dimensions:**

20"W x 26.5"D x 57"H

**20.3 cubic feet, 1 solid door**

**Voltage:** 115V 60HZ Plug Type 5-15P

**Shipping weight:** 380 lbs.



#### **Standard RIBOD1S20 - Refrigerated Incubator /BOD Chamber Features:**

- Programmable logic microprocessor controller with LCD Control Panel with message center. 4 x 20 character LCD display
- Continuous product temperature Hi/Lo alarms, audible and visual
- Programmable ramp soak feature, 2 levels of user password protection (set points and parameters), 100 event alarm logging including Date/Time Stamp and product temperatures. Stored in nonvolatile flash memory
- Integrated Hi/Lo alarm tests
- Power failure alarm
- Remote alarm contacts
- Proportional control and capacity output
- White interior, exterior, door and handle
- 5 wire shelves and bottom shelf
- 1 wire shelf adjustable
- Streamlined refrigeration design optimizes air flow and temperature uniformity
- Selectable on demand auto defrost
- Key lock door
- 2 adjustable leveling legs
- Interior light
- 1" diameter access port with plug
- 5 full width door storage compartments, 1 tilt out wire door bin
- Complete cabinet is foamed-in-place with CFC Free high density polyurethane foam insulation
- Operating temperature: -10°C to 50°C
- **Warranties:** 12 months parts

#### **Standard RIBOD1S20 - Refrigerated Incubator /BOD Chamber Options:**

- Temperature chart recorder & chart paper
- RS485 Communication output
- 4-20 MA output
- Export Crate

[www.freezerlink.com](http://www.freezerlink.com)