



## Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

[www.freezerlink.com](http://www.freezerlink.com)

### UCFM1S3-20 UnderCounter -20C Freezer

Adjustable control range: -10°C to -20°C. (Factory preset at -20°C)

Exterior Dimensions: 23.625W" x 23.5D" x 33.5H"

Interior Dimensions: 17.5W" x 16.5D" x 24H"

3.5 cubic feet – 1 solid door

Voltage: 115V/1PH 60HZ Cord & Plug NEMA 5-15P

Shipping Weight: 104lbs.

#### Standard Product Features:

- **UL and C-UL listed**; CEC California Energy Commission; Energy Star
- Thermostatic control unit with indicating control.
- Exterior front, door, top and sides are painted white.
- Interior liner and interior door panel are white, durable vacuum formed poly with seamless rounded corners for easy cleaning.
- Cabinet and door are foamed-in-place with **CFC Free high density polyurethane foam insulation**.
- Stackable design with optional stacking kit.
- Pull door handle with Door lock (2 keys)
- Magnetic door gasketing.
- 2 fixed position gray epoxy coated wire shelves
- 3 removable clear plastic drawer bins
- (2) front leveling legs
- 115/60/1 cord and plug
- Base mount refrigeration system
- **Freezer may be built in on three sides**, air intake and exhaust is through the base, top and rear of the unit.
- Compatible with laboratory case work dimensions
- Air-cooled condensing unit, **Manual Defrost**
- Drain pan evaporation, recessed kick plate, Reversible flat panel door
- **Warranty**: 12 months parts

#### Options

Digital thermometer/monitor/alarm shown, right

Stacking Kit

Export Crating

**Warranty**: 12 months parts

