



Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

www.freezerlink.com

FF2004005 Flammable Storage Freezer

24 cubic feet, 1 solid door – Energy Star Qualified

Standard Product Features:

- UL and C-UL listed; CEC California Energy Commission; **Energy Star**
- Adjustable control range from **-10°C to -25°C**
- Factory **preset at -20°C**
- Internal chamber thermometer
- Exterior front, sides, back and door are white baked on enamel
- The exterior top and bottom are galvanized steel.
- Interior liner and interior door panel are smooth aluminum.
- Cabinet and doors are foamed-in-place with **CFC Free** high density polyurethane foam insulation.
- Heavy duty spring loaded hinges.
- Key lock door.
- Full length stainless steel pull handles.
- **Four casters (2 locking).**
- 3 epoxy coated wire shelves.
- **Manual defrost.**
- Complete top mount refrigeration system.
- Cold wall evaporator.
- Air-cooled condensing unit.
- Self closing solid door.
- Magnetic door gasket.
- Door opening heaters.
- **Warranties:** 18 month parts and labor, 5 year compressor (US and Canada) 18 months parts (International).



Specifications

Interior Height	59" (149.9 cm)
Interior Width	23-1/2" (59.7 cm)
Interior Depth	30" (76.2 cm)
Overall Height*	80-3/8" (204.2 cm)
Overall Width	27-1/2" (69.9 cm)
Overall Depth	34-7/8" (88.6 cm)



Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

www.freezerlink.com

FF2004005 Flammable Storage Freezer

24 cubic feet, 1 solid door (continued)

Gross Cu. Ft.	24
Shelf Area (sq.ft.)	12.8
Number of Shelves	3
Number of Casters	4 Standard
Number of Legs	4 Optional
Condensing Unit	3/4 HP
Refrigerant	R404A
Electrical	115/60/1
Cord & Plug	Yes
Max Fuse Size	15
NEMA Plug	5-15P
Total Amp Draw	8.2
Voltage:	115V 1PH 60HZ Plug Type 5-15P
Crated Height	83-3/4" (212.7 cm)
Crated Width	37" (94.0 cm)
Crated Depth	41" (104.0 cm)
Crated Weight	382 (173.6 kg)

Options for FF2004005

LEGS	Legs in lieu of casters
BIN	Storage bin 23 x 4 x 4
EXTSS	SS Exterior (with galv. back)
SHELFNSXF	Extra shelf with clips
INTSS	Stainless steel interior
SSDRAWER	SS drawer (8 per door)
REC6DP1	Temp chart recorder/chart paper
Export Crating	For FF2004005