



Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

www.freezerlink.com

SSSG2SG52 Premium Laboratory Fridge, 4°C Two Glass Door, 52 Cu Ft Sliding Glass

External Dimensions:

55"W x 34"D x 79-5/8"H

Internal Dimensions:

51"W x 30"D x 59"H

52 cubic feet, 2 glass doors

Voltage: 115V 1PH 60HZ Plug Type 5-15P

Shipping weight: 580 lbs.

SSSG2SG52 Product Features:

- Alarm volume adjustable manually
- Digital 4x20 character LCD display
- microprocessor temperature controller, audible and visual Hi/Lo temperature alarm.
- Adjustable control range from 2°C to 10°C factory preset at 4°C.
- Remote alarm contacts, continuous product temperature display.
- 3 sensor system, 2 product, 1 air
- Power supply switch.
- Door ajar alarm, audible and visual.
- 2 to 10 volt DC output for product temperature (selectable to air temperature).
- Password protection- set-points and factory settings.
- 100 event alarm logging.
- Integrated Hi/Lo product temperature alarm test.
- Digital calibration air and product
- Real time clock with date and time display.
- Door opening counter with 24 hour automatic reset.
- Adjustable alarm beep or constant on (key pad selectable).
- Low battery test switch with buzzer.
- Fan motor run time monitor.
- Defrost heater time monitor.
- Condenser/compressor run time monitor.
- Sensor failure alarm.
- Exterior cabinet front, sides and back are painted white.
- Exterior cabinet top and bottom are galvanized steel, interior cabinet liner is painted white.
- Cabinet is foamed-in-place with CFC Free polyurethane foam insulation.
- Glass doors, full size, double pane.
- Self closing glass doors with hold open feature, key door locks, 2 keys.
- Four casters (2 locking).
- 3 coated wire shelves per door section, interior light, switch activated.
- Air cooled condensing unit, top mounted forced air refrigeration system, automatic defrost and condensate evaporation.
- Sensor access port, 1" diameter.
- Warranties: 24 month parts and labor, 5 year compressor.
- UL/CUL listed
- CEC Listed*





Industrial Freezer Sales

A division of IDS

5311 Derry Avenue Building D Agoura Hills CA 91301

Phone (818) 597-4300 Fax (818) 597-4301

www.freezerlink.com

SSSG2SG52 Premium Laboratory Fridge, 4°C Two Glass Door, 52 Cu Ft Sliding Glass

SSSG2SG52 Laboratory Sliding Glass Fridge Optional Features

- Extra shelf
- Legs 6" in lieu of casters
- Stainless steel interior
- Stainless steel exterior
- Access port 2" sleeve with cover
- Internal electrical outlet
- Temperature chart recorder with chart paper
- 4-20ma output for product temperature (selectable to air temperature)
- RS-485 digital communications port (MODBUS-RTU)
- Ethernet 10 baseT (HTTP) control. monitoring web card
- Seismic mounting kit
- Export crating



** Tested to meet the Maximum Daily Energy Consumption Requirements (KWhr/day) as defined by the California Energy Commission Appliance Efficiency Regulations and ENERGY STAR® Program Requirements for Commercial Refrigerators and Freezers.*